

LEONIS IP65 1-KIT 2700K | DOWNLIGHT | BRUSHED NICKEL

2310016055

nordlux®



Voltage (V): 220-240 Volt	Height (cm): 3.6	Sales Box Height (cm): 13
IP degree: IP65	Width (cm): 8.5	Sales Box Width(cm): 13
Class (Class 1, Class 2, Class 3): Class 2 (Double isolated)	Built In Spot Diameter (cm): 8.5	Sales Box Depth (cm): 50
Bulb base: LED Module	Mount directly into insulation: False	Sales Box Volume m³ : 0.0084
Dimmerable: False		Product net weight (kg): 0.0766
Parallel connection: True	EAN: 5704924015199	Brightness of light (Lumen): 345
	TUN: 2319285	Color Temperature (K): 2700K
Primary material: Plastic	Item Number: 2310016055	Ra-value : 80
Secondary material: Plastic	Pcs Per Master Carton: 3	Lifetime (h): 20000
Color: Brushed Nickel		Beam Angle (°) : 110
		Candela (cd) (for directional lamp only): 0
		Energy Class: G
		Actual Watt (W): 4.5

- Suitable for the bathroom (IP65) • Easy installation
- Parallel connection possible • 5-year LED guarantee

Leonis is a simple downlight with a low installation height. With integrated LED, a plastic frame and a warm, white light (2700 kelvin).

Leonis is quick and easy to install, has a flexible cutting diameter (68–73/76mm) and allows for parallel connection.

The high protection rating (IP65) means Leonis is particularly suitable for the bathroom.